


High speed bar taking machine EFFECI 1900 FSS/IP430




- Sewing area 40x30mm
- Exchangeable clamp with magnetic movement
- Max speed 3000 rpm
- Electronic thread tensioner
- Dry lubrication system
- New touch screen panel for machines' functions setting and programming directly on the machine
- Low energy consumption
- Is possible to realize vertical bar tacking machine by replacing the presser foot
- o Is possible to turn the machine into a button sewer by replacing the clamp
- Long lasting reliability
- Integrated motor
- Expandable internal storage by USB input














Technical characteristics EFFECI 1900FSS/IP430

Electronic thread tensioner



Is possible to store several tension levels depending on used fabric. By selecting the desired one, the electronic thread tensioner will automatically adjust the thread tension.

Touch screen panel



Big sized touch screen panel, suitable to program sewing pattern and data directly on the machine.

Magnetic movement clamp



The magnetic clamp ensure high performances and precision during working cycles.
Replacing the clamp is possible to realize vertical bar tacking works.

Optional button sewer KIT



The machine, on request, is supplied with button sewer KIT. By replacing some parts of the clamp is possible realize button sewing jobs.

Head	EFFECI 1900FFS/IP430 bar tacking machine
Motor	Integrated
Max. speed	3000 rpm
Working area	40mm x 30mm
Application	Medium/Light
Hook type	Shuttle hook
Feed mechanism	Step-motor
Max. stitch length	From 0.1mm to 10mm
Programming	Directly on the machine by using touch panel
N. of storable programs	50 standard, up to 200 custom
Presser foot lift	14mm
Presser foot lift mechanism	Electronic with step-motor
Thread trimmer mechanism	Automatic
Needle system	134R/135X17
Needle size	80/110
Weight	100Kg (head and motor)
Voltage	220V single phase

www.fuse.it