

- Electronic thread tension
- Rotary double capacity hook
- Excellent sewing quality which fully represents ornamental programmed sewing
- Max sewing speed 2.700 rpm
- New touch screen panel to set machine functions and sewing patterns directly on the machine
- Low Energy consumption
- Compatible with Brother, Juki or Mitsubishi programs
- Long time granted reliability
- Frame detection Scanner with automatic pattern setting
- Using a 550W power electric motor the machine guarantee a needle penetration even on difficult fabrics







Technical characteristics Effeci 400-4530H-01

Jumping foot



Foot leverage amount and pressure could be modified using the touch screen panel, no particular tools required.



Big sized touch screen panel, suitable to program sewing pattern and data directly on the machine.

Breaking thread sensor



Thanks to breaking thread sensor, the machine will stops automatically alerting the operator.

Sewing patterns upload

Touch-Screen panel



Easy sewing patterns upload by using USB port or SD card. The internal storage can hold up to 512 sewing patterns.



<u>400- 4530H-01</u>

FOR HEAVY MATERIALS

SEWING FIELD

PATTERN SEWING MACHINE TYPE

| Pattern lock-stitch machine |
|---|
| Rotary, double capacity |
| Max sewing speed 2.700 rpm |
| Max. 450x300mm |
| Motors and encoder |
| From 0,05mm to 12,7 mm |
| 20.000 points |
| USB port or SD card |
| Max. 512 patterns in the internal storage |
| Pneumatic, 30mm |
| 22mm |
| Included – standard |
| Included – standard |
| AC servo 550W Direct Drive |
| 198 Kg |
| 220V monophase |
| 0,5 Mpa 1,8/L/min |
| |

www.fuse.it